Product data sheet

Specifications



Network Management Card 3 (NMC3) for Easy UPS On-Line, 1-Phase, secure remote UPS monitoring and management

AP9544

Overview

Presentation

The Network Management Card for Easy UPS On-Line (AP9544) enables secure remote monitoring and control of one Easy UPS Online through the easy-to-use web browser interface, via EcoStruxure™ IT Software or another SNMP-enabled system.

A 12-month Secure NMC Subscription, that allows the customer to access future firmware updates, is included with the purchase of the card*. Upon expiration of the provided Secure NMC Subscription the purchase of a new Secure NMC Subscription is required to access future firmware updates.

*The NMC Firmware must be V2.5 or later. Find the latest Firmware in the Software and Firmware section below.

Main

Range of product	Network Management Cards
Range compatibility	Easy UPS On-Line Easy UPS 1 Ph On-Line
Product or component type	Device monitoring and management
Provided equipment	Micro-USB cable Installation manual
Number of input phases	1
Standards	CISPR 32 VCCI class A ICES-003 EN 55024 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-4-8 EN 61000-6-2 EN/IEC 62040-2

Physical

Net weight	0.05 kg
Width	5.2 cm
Height	4.4 cm
Depth	8.0 cm

Conformance

Product certifications	FCC Class A AS/NZS UK PSTI

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Storage Relative Humidity	0…95 %
Relative humidity	0…95 %
Ambient air temperature for storage	-15…65 °C
Ambient air temperature for operation	-5…45 °C
Storage altitude	0…15240 m
Operating altitude	0...10000 ft

Communications & Management

Communication network type	10/100/1000BASE-T
Authentication	Radius
Communication port protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.600 cm
Package 1 Width	16.500 cm
Package 1 Length	23.000 cm
Package 1 Weight	284.000 g
Unit Type of Package 2	S06
Number of Units in Package 2	44
Package 2 Height	68.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	21.000 kg

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**69 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**3 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**66 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**F4c2965e-f80d-4830-8cd4-be926afb0f45**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
End of life manual availability	End of Life Information
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**